

Table of Contents

- 2. Background and Related Work** 3
- 2.1 Introduction 3
- 2.2 Products 3
- 2.3 Research 5
- 2.4 Comparative analysis 7
- 2.5 Summary 9

2. Background and Related Work

2.1 Introduction

This chapter presents the background research done to develop Connect. It covers:

- **Interactive urban light installations:** Public art installations that respond to human presence in real time, where strangers collectively shape a shared visual environment through light and colour.
- **Community stories:** Projects that use everyday technology to connect strangers in a shared space through participation and co-creation.
- **Participatory public art:** Research into design principles that create a sense of connection between strangers in shared spaces.
- **Research:** Academic studies and technical documentation covering loneliness in urban environments, velostat as a pressure-sensing material, the ESP32 microcontroller family, CAN bus communication and addressable LED components.
- **Comparative analysis:** A structured overview of the products, installations, and sources reviewed in this chapter, summarising their relevance to Connect.

2.2 Products

2.2.1 Interactive urban light installations

Kinetic particles is an interactive art installation that connects human physical movement with digital projections [1]. By using cameras and deep learning technology, the system tracks the body movements of performers and audience members in real-time, as illustrated in Figure 1. This tracking data is then used to control words and letters that are projected onto the walls of the room. When people move, their gestures (like the speed of their wrists) act like a force that pushes the projected text around, turning the words into moving particles. The project is designed to be an immersive experience where multiple people can explore the connection between their physical actions and the digital environment, allowing them to collaborate and interact with each other. This article is highly relevant to our research because both projects use technology to create a shared, physical experience rather than isolating people. In the “Kinetic particles” installation, multiple spectators can simultaneously interact with an immersive digital environment. The authors note that this collective setup invites people to collaborate and synchronize their movements. This directly connects to our idea of blending passengers' light colors in the metro. Additionally, the project demonstrates that giving intuitive, real-time visual feedback based on physical actions creates a lively and organic interaction. We can use these findings as proof that interactive design can effectively pull people out of their digital bubbles and connect them with strangers.



Figure 1: Kinetic Particles installation: text particles responding to audience movement [2]

2.2.2 Community stories

This article describes the project Keitai Trail in which researchers used mobile phones to collect and link personal stories from people in public spaces [3]. During an art festival, the researchers made a workshop, seen in Figure 2. Here participants recorded short videos based on a specific question-and-answer game. Each person answered a question from a previous participant, shared a short story, and then posed a new question for the next participant. All these connected stories were then projected onto a large screen so that participants could view the entire network of videos. The aim was to change users' mindsets by using everyday mobile phones as creative means of expression rather than just for one-way communication [4].

This research is relevant to our project because it demonstrates how technology can be used to collect stories from strangers and connect them in a shared environment. Similar to our concept with QR codes and voice memos in the underground, this project utilises an everyday device to lower the threshold for participation and capture human experiences in an “expression mode”. The authors show that providing a clear structure, such as answering a question from a predecessor, acts as an incentive to help people share their thoughts. Furthermore, making these connections visible helps participants understand that their own story has an impact on the bigger picture and that they are part of the world around them. We can use this scientific insight to substantiate that our asynchronous audio system will indeed offer travellers a sense of community and connection.



Figure 2: Project installation [5]

2.2.3 Participatory Public Art

This article outlines the evolution of materials used in public art and how new technologies have led to interactive and participatory installations [6]. The authors categorize art forms into static, dynamic, interactive, and participatory levels. In participatory forms, artists do not just create a final object; they design a platform that grows through the creative input of the public. The paper highlights several design cases to illustrate this concept. One example is “Strijp-T-together”, an installation designed for a creative industrial area. It uses a mobile app where users can draw or add graphics to a photo of the main hall. These additions are then projected into the physical space and appear on other users' phones, encouraging people to react to each other's drawings and stimulating social interaction among individuals from different companies (see Figure 3). Another example, “Leave Your Mark”, uses projection mapping and a live camera feed to connect two different locations in a city, allowing a person walking by to see a stranger “drawing” on the installation elsewhere, aiming to increase feelings of inclusion and connectedness. This article is relevant to Connect because it provides a theoretical framework for participatory public art. The examples demonstrate that combining a physical environment with a digital, co-creative layer can foster social interaction between strangers in a shared space. This supports the argument that Connect's approach, where passengers collectively shape a visual environment through touch follows an established design principle for creating a sense of shared presence.



Figure 3: Striip-T-together installation: participants co-creating a shared digital environment through a mobile app [7]

While these installations demonstrate how interactive systems can foster shared experiences, they rely on large-scale sensing technologies such as cameras and projection systems. In contrast, Connect translates these principles into a distributed embedded system suitable for a metro environment, using touch-based sensing, microcontrollers, and LED feedback.

2.3 Research

2.3.1 Loneliness in public spaces

A central motivation behind Connect is the observation that people in dense urban environments such as metro carriages, often feel more disconnected from those around them, not less. This paradox is supported by the research article “Lonely in a crowd” [8], who investigated the real-time relationship between loneliness and the social environment, published in Scientific Reports. Using a smartphone-based assessment method, 756 participants across multiple countries reported their momentary feelings of loneliness up to three times daily over 14 days, alongside observations about their immediate environment [9].

The study found that perceived overcrowding was positively associated with loneliness (OR: 1.39), meaning that being surrounded by many people did not reduce feelings of isolation, it increased them. In contrast, perceived social inclusivity, defined as feeling welcome, feeling that others would help you, and sensing shared values with those nearby, was significantly associated with lower loneliness (OR: 0.79). Contact with nature similarly reduced loneliness (OR: 0.72), and the two effects amplified each other when combined [10].

The findings from this study highlights the problem we want to solve with our project. They suggest that placing people in proximity to one another is not enough to create a sense of belonging, what matters is whether people feel acknowledged and included by those around them [11]. We aspire to address this by creating a shared experience that makes the presence of fellow passengers visible and meaningful, without requiring explicit social interaction. Rather than demanding conversation or eye contact, it uses light as a medium to signal to passengers that they are part of a collective moment.

It should be noted that the study has limitations. The sample was self-selected and the main

participants was educated, middle-aged, Caucasian participants, which limits how broadly the findings can be generalized. Loneliness was also measured with a single survey item, and the study is observational, meaning the associations found do not establish causation. Still, the core finding, that overcrowding increases loneliness while perceived inclusivity reduces it, provides a meaningful theoretical basis for our project.

2.3.2 Microcontroller

The decision to use a microcontroller from the ESP32 family is supported by a comparative analysis of microcontroller platforms for IoT and embedded systems [12]. The study evaluates the ESP32 against comparable boards and concludes that its combination of low cost, low power consumption, and compatibility with the Arduino development environment makes it well suited for sensor-driven embedded applications.

In Connect, the system is distributed across two types of nodes: sensor nodes embedded in each handrail pole, and a central ceiling node that drives the LED strip. Each node handles one task: either reading pressure input from the velostat sensor, or sending colour signals to the LED strip. A single-core microcontroller is sufficient for this, as no parallel processing is required at the node level. The ESP32 microcontroller can handle multiple tasks simultaneously [13], which is not necessary for our project. Therefore we use the WEMOS mini, a development board based on the ESP32-C3 is used for this. It is a single-core RISC-V variant in the ESP32 family. This was chosen due to its compact form factor and lower power consumption compared to the dual-core original [14].

The Arduino-compatible development environment shared across the ESP32 family is a practical advantage for our multidisciplinary student team, as it is «beginner-friendly» and have several libraries for both sensor input and LED control [15].

2.3.3 Velostat sheet

The decision to use velostat sheets for touch detection in the handrails of Connect is grounded in established research on flexible piezoresistive materials. Velostat is a polyethylene-carbon composite material that changes its electrical resistance in response to applied pressure. When compressed, the resistance decreases, producing a measurable electrical signal [16] Dzedzickis et al. evaluated the mechanical and electrical characteristics of velostat as a tactile sensor material, testing it under static, long-term, and cyclic load conditions.

The results confirm that velostat produces consistent, repeatable signals across multiple loading cycles, and that it can be implemented using a simple electrode pair [17]. These properties make it well suited for Connect, where the sensor must reliably detect the pressure of a passenger gripping a handrail and produce a signal the ESP32 can read.

A practical advantage of velostat for this application is its flexibility. The material is thin and can conform to curved surfaces such as a handrail without requiring rigid mounting. One limitation noted in the research is that velostat's response is not perfectly linear and may drift slightly under repeated use [18]. To account for this, the sensor node includes a 10 kΩ potentiometer that allows the sensitivity to be manually adjusted during prototyping until reliable detection is achieved.

2.3.4 CAN Bus and MCP2551 transceiver

Connect uses a distributed node architecture: each handrail pole contains an independent sensor node, and a central node at the ceiling receives their signals and controls the LED strip. Coordinating these nodes requires a communication protocol that can handle multiple transmitters on a shared line and remain reliable in an electrically noisy environment.

CAN (Controller Area Network) is a serial communication protocol originally developed for automotive applications, where multiple electronic control units must communicate reliably despite high levels of electrical interference [19]. It is standardised under ISO 11898 and is widely used in embedded systems beyond the automotive industry, including industrial and building automation contexts [20]. Of particular relevance to Connect is CAN's use of differential signalling: the bus carries each signal across two lines with opposite voltages, so interference affects both lines equally and is cancelled out at the receiver [21]. This makes CAN significantly more robust against electromagnetic noise than single-ended alternatives, which is important in the context of a metro carriage.

The MCP2551 is a high-speed CAN transceiver developed by Microchip Technology that implements the physical layer of the ISO 11898 standard [22]. It acts as the interface between the microcontroller's digital TX/RX pins and the differential CAN bus line. One unit is placed at each node both the sensor nodes in the poles and the central ceiling node.

2.3.5 WS2812B addressable LED strip

The WS2812B is an individually addressable RGB LED component that integrates the control circuit and the RGB emitter into a single 5050-format package [23]. Each unit contains a built-in driver IC that receives colour data, applies it to its own output, and passes the remaining data to the next unit in the chain via a single data line. This daisy-chain architecture means the entire ceiling strip can be controlled from one digital output pin on the microcontroller [24].

Individual addressability is essential for Connect's core interaction: each passenger's contact with a handrail must produce a distinct colour that travels visibly up the pole and merges with others across the ceiling. The WS2812B supports 256 brightness levels per colour channel, giving a total of approximately 16.7 million possible colours [25].

The strip is compatible with the FastLED library available in the Arduino development environment, which is consistent with the microcontroller platform used across the rest of the system.

Connect consists of multiple distributed sensor nodes embedded in handrails, each detecting passenger interaction through velostat sensors. These nodes communicate via a CAN bus network to a central controller located in the ceiling, which drives an addressable LED strip to visualise collective interaction.

2.4 Comparative analysis

The sources reviewed in this chapter fall into two groups: installations and products that are relevant to the design of Connect, and research or technical literature that informs the component choices. These are summarised in table 1 and table 2.

The three installations in 1 each highlight something relevant to Connect. Kinetic Particles shows that

giving people real-time visual feedback based on their physical actions can pull them into a shared experience. Keitai Trail shows that people are more willing to participate when the interaction uses something familiar, like a phone. Strijp-T-together is the closest to what Connect is trying to do: it shows that adding a co-creative digital layer to a physical space can get strangers to interact in a meaningful way.

In 2, the study by Hammoud et al. is the main theoretical motivation for the project. It shows that being surrounded by people does not make you feel less lonely, what matters is whether you feel noticed and included. The other entries in the table are more technical. Maier et al. informed the choice of microcontroller platform, Dzedzickis et al. supports the use of velostat for detecting grip pressure, and Bozdal et al. explains why CAN bus is a good fit for a system that needs to stay reliable in an environment with a lot of electrical noise. The MCP2551 and WS2812B datasheets document the specific components used for the CAN bus connection and the LED output.

Table 1: Products & Installations

Category	Technology/Medium	Interaction Type	Core Focus	Relevance to Connect
Kinetic Particles	Cameras, deep learning, digital projections	Real-time physical movement	Connecting physical movement with a digital environment	Proves that real-time visual feedback pulls people out of their digital bubbles
Keitai Trail	Mobile phones, large projection screens	Asynchronous (recording Q&A videos)	Collecting and linking personal stories	Supports the use of everyday devices to foster a sense of community
Participatory Installations (Strijp-T-together)	Mobile apps, projection mapping, live camera feeds	Real-time and asynchronous digital co-creation	Stimulating social interaction through a shared platform	Provides a theoretical framework for passengers co-creating their metro environment

Table 2: Research & Technical Literature

Category	Method	Key Finding	Relevance to Connect
Hammoud et al. - Lonely in a Crowd	Smartphone-based ecological momentary assessment	Overcrowding increases loneliness; perceived inclusivity reduces it	Confirms the problem Connect aims to address
Maier et al. - ESP32	Comparative analysis of microcontrollers for IoT	ESP32 family offers low cost, low power consumption, and Arduino compatibility for embedded applications	Justifies the choice of the WEMOS C3 mini for the sensor and ceiling nodes
Dzedzickis et al. - Velostat	Mechanical and electrical testing under static, long-term, and cyclic load conditions	Velostat produces consistent, repeatable signals and can be implemented with a simple electrode pair	Justifies the use of velostat sheets for pressure detection in the handrails
Bozdal et al. - CAN Bus	Survey of CAN protocol properties and security	CAN's differential signalling provides strong immunity to electrical noise and interference	Justifies the use of CAN bus for communication between nodes in a metro environment

Category	Method	Key Finding	Relevance to Connect
Microchip Technology - MCP2551	Component datasheet	Implements the ISO 11898 physical layer, acting as the interface between microcontroller and CAN bus	Justifies the choice of transceiver for each node in the system
WorldSemi - WS2812B	Component datasheet	Individually addressable RGB LED with integrated driver, controllable via a single data line	Justifies the choice of LED component for producing distinct, blendable colours on the ceiling

2.5 Summary

This chapter has reviewed existing installations, research, and technical literature relevant to Connect. Interactive installations such as Kinetic Particles and Strijp-T-together demonstrate that real-time visual feedback based on physical interaction can effectively create a sense of shared presence between strangers. Keitai Trail shows that everyday devices can lower the threshold for participation and foster community through co-creation.

The research by Hammoud et al. provides the core theoretical motivation for the project: overcrowding alone does not reduce loneliness, what matters is whether people feel acknowledged and included. This finding directly informs the design goal of Connect.

On the technical side, the literature and component documentation support the use of velostat sheets for pressure detection in the handrails, the WEMOS C3 mini as a low-power microcontroller suited to single-task embedded nodes, CAN bus as a noise-resistant communication protocol for a distributed multi-node system, and the WS2812B as an addressable LED component capable of producing individually controlled colours across the ceiling strip.

Together, these sources establish both the problem Connect aims to address and the technical foundation for how it will be built.

[1], [2] Mickael Lafontaine, Julie Cloarec-Michaud, Kevin Riou, Yujie Huang, Kaiwen Dong, Patrick Le Callet, 2023. *Kinetic particles: from human pose estimation to an immersive and interactive piece of art questioning thought-movement relationships..* New York, NY, USA: Association for Computing Machinery, ISBN 9798400700286.

[3], [4], [5] Kosuke Numa, Tatsuo Sugimoto, Masako Miyata, Kiyoko Toriumi, Jun Abe, Yuri Tanaka, Sumaru Niida, Koichi Hori, 2009. Using common devices as collaborative tools for collecting and connecting people's stories. *2009 International Conference on Innovations in Information Technology (IIT)*, pp.115-119.

[6], [7] Jun Hu, Mathias Funk, Yu Zhang, Feng Wang, 2014. Designing Interactive Public Art Installations: New Material Therefore New Challenges. *Entertainment Computing - ICEC 2014*, Berlin, Heidelberg: Springer Berlin Heidelberg, pp.199-206, ISBN 978-3-662-45212-7.

[8], [9], [10], [11] Ryan Hammoud, Stefania Tognin, Ioannis Bakolis, Daniela Ivanova, Naomi Fitzpatrick, Lucie Burgess, Michael Smythe, Johanna Gibbons, Neil Davidson, Andrea Mechelli, dec 2021. *Lonely in a crowd: investigating the association between overcrowding and loneliness using smartphone technologies.* *Scientific Reports*, 11, pp.24134, ISSN 2045-2322.

[12], [13], [15] Alexander Maier, Andrew Sharp, Yuriy Vagapov, 2017. Comparative analysis and practical implementation of the ESP32 microcontroller module for the internet of things. *2017 Internet Technologies and Applications (ITA)*, pp.143-148.

[14] Espressif Systems, 2023. *ESP32-C3 Series Datasheet: Ultra-Low-Power SoC with RISC-V Single-*

Core CPU.

[16], [17], [18] Andrius Dzedzickis, Ernestas Sutinys, Vytautas Bucinskas, Urte Samukaite-Bubniene, Baltramiejus Jakstys, Arunas Ramanavicius, Inga Morkvenaite-Vilkonciene, 2020. [Polyethylene-Carbon Composite \(Velostat®\) Based Tactile Sensor](#). *Polymers*, 12, ISSN 2073-4360.

[19], [21] Mehmet Bozdal, Mohammad Samie, Sohaib Aslam, Ian Jennions, 2020. Evaluation of CAN Bus Security Challenges. *Sensors*, 20, MDPI.

[20] *ISO 11898-1: Road Vehicles — Controller Area Network (CAN)*. 2015.

[22] Microchip Technology, 2007. [MCP2551 High-Speed CAN Fault-Tolerant Transceiver](#).

[23], [24], [25] WorldSemi, 2016. [WS2812B Intelligent Control LED Integrated Light Source](#).

From:

<https://www.eps2026-wiki5.dee.isep.ipp.pt/> - **EPS@ISEP**

Permanent link:

<https://www.eps2026-wiki5.dee.isep.ipp.pt/doku.php?id=report:soa>

Last update: **2026/04/12 12:30**

